

Fence Care Oil

General Product Description

Product description	bio pin Fence Care Oil is a special high-quality, solvent-free oil for wooden outdoor elements such as fences, pergolas etc. High-quality vegetable oils impregnate new oil and add new shine to old wood. Mineral pigments ensure an attractive appearance and protect the wood from early ageing. Does not contain any wood preservative.
Areas of application	For untreated, pressure treated and oiled wood for outdoor applications. Not suitable for oak and sealed or otherwise non-absorbent wooden surfaces.
Constituents	Binding agents: Linseed oil-stand oil, wood oil Solvent: Water Pigments: Mineral pigments Additives: Methyl cellulose, vegetable-based emulsifier, lead and barium-free drying agents
Colour:	brown No. 40913
Storage:	Keep tightly sealed and out of the reach of children. Store in cool but frost-free
Shelf-life:	A minimum of 2 years if tin is kept firmly sealed.
Can sizes:	5 ltr
Class of risks:	Does not apply, no hazardous good according to GefStoffV (German Ordinance on Hazardous Goods) and VbF

Technical Data

Specific weight	Approx. 0.98 g/ml (depending on colour)
Viscosity	Approx. 12 seconds (DIN-size beaker 4 mm) at 20°C.
Flashpoint	above 200°C
Consumption	Approx. 70-80 ml/m ² per coat depending on condition of surface and absorption of material. Consumption may be considerably higher for rough sawn surfaces.
Drying time	At 20° C and average humidity dry and re-coatable after 6-8 hours.
How to use	
Suitable surfaces	Wood (see also ‚Area of application‘)
Surface requirements	The surface must be dry and free of dust and grease.
Application:	Only use if temperature is above 10°C. Stir well before use. Evenly apply thin coat.
Thinner	Product comes ready for use. If necessary dilute with water.
Pre-treatment:	Completely remove old paint and stain surfaces, grey wood should be sanded down to healthy wood. New pressure-treated wood should be left to season for one or two months and any salt crystals should be removed with a brush.

Fence Care Oil

New coats	Apply one coat of bio pin Fence Care Oil for initial treatment on pre-oiled wood and two to three coats to pressure-treated and untreated wood.
Renovation of old wood	Clean and prepare wooden surfaces in accordance with their condition. Evenly apply one to two thin coats of bio pin Fence Care Oil.
Cleaning of tools	Clean all tools immediately with water and soap.
Safety Advice	Keep tightly sealed and out of the reach of children. In certain circumstances oils may self-ignite while drying. Cloths used during application of hard oil must not be crumpled but must be spread out and dried in fresh air or soaked in water before disposal.
Disposal of product	Do not empty bio-degradable and solvent-free paints etc. into drains or onto soil. Completely dried product remnants can be disposed of in the normal way. Empty tins can be recycled.